

M60 Series

60W 2:1 Regulated Single output



Features

- Wide 2:1 Input Range
- 1600VDC Isolation
- No Minimum Load Required
- Efficiency up to 91%
- -40 ~ 85°C Operation Temperature Range
- Adjustable Output Voltage
- Remote On/Off Control (CTRL)
- Continuous Short Circuit Protection
- Over Current Protection
- Over Voltage Protection
- Over Temperature Protection
- Soft Start
- Built-in EMC filter meets EN55032 ClassA without external components
- Optional Heat-sink



The M60 series is a family of high performance 60W single output DC-DC converters. These converters combine nickle-coated copper package in a 2"x2" case with high performance features such as Active Clamp Technology, continuous short circuit protection with automatic restart and tight line/load regulation. Devices are encapsulated using flame retardant resin. Input voltages of 24 and 48 with output voltage of 3.3, 5, 12, 15Vdc. High performance features include high efficiency operation up to 91% and output voltage accuracy of $\pm 1\%$ maximum.

ALL SPECIFICATIONS ARE TYPICAL AT 25°C, NOMINAL INPUT AND FULL LOAD UNLESS OTHERWISE NOTED.

OUTPUT SPECIFICATIONS		
Output Voltage Accuracy		$\pm 1\%$, max.
Output Voltage Adjustability (Trim) (1)		$\pm 10\%$, max.
Output Current		See table, max.
Line Regulation		$\pm 0.5\%$, max.
Load Regulation (0% to 100% FL)		$\pm 0.5\%$, max.
Ripple&Noise (2)	3.3V&5.0V output	75mVpk-pk, max.
	12V&15V output	100mVpk-pk, max.
Over Voltage Protection (Zener diode clamp)	3.3V output	3.9V
	5V output	6.2V
	12V output	15V
	15V output	18V
Over Load Protection		135% of FL, typ.
Short Circuit Protection		Indefinite(hiccup) (Automatic Recovery)
Temperature Coefficient		$\pm 0.02\%/^{\circ}\text{C}$
Capacitive Load (3)		See table, max.
Transient Recovery Time (4)		250 μs , typ.
Transient Response Deviation (4)		$\pm 3\%$, max.

INPUT SPECIFICATIONS		
Input Voltage Range		See table
Under Voltage Lockout		
24 Models	Module ON / OFF	17.8Vdc / 16Vdc, typ.
48 Models	Module ON / OFF	33.5Vdc / 30.5Vdc, typ.
Start up Time (Nominal Vin and constant resistive load)		20mS, typ.
Input Filter		Pi Type
Input Current (No-Load)		See table, max.
Input Current (Full-Load)		See table, typ.
Input Reflected Ripple Current (5)		20mApk-pk, typ.
Remote On/Off (CTRL) (6)		
ON: 3.0 ... 12Vdc or open circuit		
OFF: 0 ... 1.2Vdc or Short circuit pin 2 and pin 3		
OFF idle current: 5.0mA, typ.		

ABSOLUTE SPECIFICATIONS (7)		
These are stress ratings. Exposure of devices to any of these conditions may adversely affect long-term reliability.		
Input Surge Voltage (100mS)		
24 Models		50Vdc, max.
48 Models		100Vdc, max.
Soldering Temperature (1.5mm from case 10sec max.)		260°C, max.

GENERAL SPECIFICATIONS		
Efficiency		See table, typ.
I/O Isolation Voltage (60sec)		
Input / Output		1600Vdc
Case / Input & Output		1600Vdc
Isolation Resistance		1000M Ω , min.
Isolation Capacitance		2000pF, typ.
Switching Frequency		270kHz, typ.
Humidity		95% rel H
Reliability Calculated MTBF (MIL-HDBK-217 F)		>110Khrs
Safety Standard (design to meet)		IEC/EN 60950-1



EMC CHARACTERISTICS		
Radiated Emissions	EN55032	CLASS A
Conducted Emissions	EN55032	CLASS A
ESD	IEC61000-4-2	Perf. Criteria A
RS	IEC61000-4-3	Perf. Criteria A
EFT (8)	IEC61000-4-4	Perf. Criteria A
Surge (8)	IEC61000-4-5	Perf. Criteria A
CS	IEC61000-4-6	Perf. Criteria A
PFMF	IEC61000-4-8	Perf. Criteria A

PHYSICAL SPECIFICATIONS		
Case Material		Nickel-coated Copper
Base Material		Non-conductive Black Plastic (UL94V-0 rated)
Pin Material		$\Phi 1.0\text{mm}$ Brass Solder-coated
Potting Material		Epoxy (UL94V-0 rated)
Weight		70.0g
Dimensions		2.00"x2.00"x0.40"

ENVIRONMENTAL SPECIFICATIONS		
Operating Ambient Temperature		
-40°C ~ +85°C(See Derating Curve)		
-40°C ~ +40°C(For 100% load)		
Maximum Case Temperature		110°C
Thermal Impedance (Nature Convection)	Without Heat-sink	10.5°C/W
	With Heat-sink	8.4°C/W
Storage Temperature		-55°C ~ +125°C
Over Temperature Protection (Case)		120°C, typ.
Cooling (9)		Nature Convection

M60 - 60W 2:1 Regulated Single output

PART NUMBER STRUCTURE



MODEL SELECTION GUIDE

MODEL NUMBER	INPUT Voltage Range (Vdc)	INPUT Current		OUTPUT Voltage (Vdc)	OUTPUT Current		EFFICIENCY @ FL (% , typ.)	Capacitor Load @FL (μF, max.)
		No-Load (mA, max.)	Full Load (mA, typ.)		Min. load (mA)	Full load (mA)		
M60-243R3S60	18-36	80	2151	3.3	0	14000	91	36000
M60-2405S60	18-36	100	2762	5	0	12000	91	20400
M60-2412S60	18-36	40	2793	12	0	5000	90	3550
M60-2415S60	18-36	40	2793	15	0	4000	90	2300
M60-483R3S60	36-75	50	1075	3.3	0	14000	91	36000
M60-4805S60	36-75	60	1389	5	0	12000	91	20400
M60-4812S60	36-75	40	1397	12	0	5000	91	3550
M60-4815S60	36-75	40	1397	15	0	4000	91	2300


NOTE

1. Maximum output deviation is 10% inclusive of remote sense and trim. If remote sense is not being used, the +sense should be connected to its corresponding +OUTPUT and likewise the -sense should be connected to its corresponding -OUTPUT.
2. Measured with 20MHz bandwidth and 1.0μF ceramic capacitor.
3. Tested by minimal Vin and constant resistive load.
4. Tested by normal Vin and 25% load step change (75%-50%-25% of Io).
5. Measured Input reflected ripple current with a simulated source inductance of 12μH.
6. The remote on/off control pin is referenced to -Vin(pin2).
7. Exceeding the absolute ratings of the unit could cause damage. It is not allowed for continuous operating.
8. An external filter capacitor is required if the module has to meet IEC61000-4-4 and IEC61000-4-5. The filter capacitor Motien suggest: Nippon chemi-con KY series, 220μF/100V.
9. "Nature Convection" is usually about 30-65 LFM but is not equal to still air (0 LFM).

TEST CONFIGURATIONS


Input Reflected Ripple Current Test Step

Input reflected ripple current is measured through a source inductor L_{in} ($12\mu H$) and a source capacitor C_{in} ($47\mu F$, $ESR < 1.0\Omega$ at $100KHz$) at nominal input and full load.



Output Ripple & Noise Measurement Test


Use a capacitor C_{out} ($1.0\mu F$) measurement. The Scope measurement bandwidth is 0-20MHz.



DESIGN & FEATURE CONFIGURATIONS


Output Ripple & Noise Reduction

To reduce ripple and noise, it is recommended to use a $1\mu F$ ceramic disk capacitor and a $10\mu F$ electrolytic capacitor to at the output.



CTRL Module ON / OFF

Positive logic turns on the module during high logic and off during low logic. Ctrl module on/off can be controlled by an external switch between the ctrl terminal and -Vin terminal. The switch can be an open collector or open drain. For positive logic if the ctrl feature is not used, please leave the ctrl pin floating.



Over Voltage Protection

The module includes an internal output over voltage protection circuit, which monitors the voltage on the output terminals. If this voltage exceeds the over voltage set point, the module will activate the control loop of internal circuit to clamp the output voltage.





Over Current Protection

The module includes an internal over current protection circuit, which will endure current limiting for an unlimited duration during output over load condition. If the output current exceeds the OCP set point, the module will shut down automatically (hiccup).


The module will try to restart after shut down. If the over load condition still exists, the module will shut down again.

M60 - 60W 2:1 Regulated Single output

ELECTRICAL CHARACTERISTIC CURVES




MECHANICAL SPECIFICATIONS



PIN CONNECTIONS	
PIN NUMBER	SINGLE
1	+Vin
2	-Vin
3	CTRL
4	-Sense
5	+Sense
6	+Vout
7	-Vout
8	Trim

EXTERNAL OUTPUT TRIMMING

Output can be externally trimmed by using the method as below.




All dimensions are typical in millimeters (inches).

1. Pin diameter: 1.0 ± 0.05 (0.04 ± 0.002)
2. Pin pitch and length tolerance: ± 0.35 (± 0.014)
3. Case Tolerance: ± 0.5 (± 0.02)

MECHANICAL SPECIFICATIONS

With Heat-sink



Order code: M60-XXXXS60SK(contain: heat-sink, thermal pad)
 Material: Aluminum
 Finish: Anodic treatment (black)
 Weight: 22g (0.78oz) (without converter)

Note:

1. Converters will be supplied with heat-sinks already mounted.
 Please contact factory for quotation.